

Receiving Report

Date: 16-6-6.

Batch No: 134937

Supplier: Air Dynamics

Dart P/O: 32240

Packing Slip: Yes ☒ No ☐
 Invoice: Yes ☒ No ☐
 Receipt: Cash ☐ Cr ☒
 New Supplier Yes ☐ No ☒

Release Note Attached: Yes ☒ No ☐ N/A ☐
 Waybill Attached: Yes ☒ No ☐
 Shipment Complete: Yes ☒ No ☒ N/A ☒
 QC18 Inspection ☐ N/A ☒
 Work Order ☐ N/A ☒

Discrepancies

Part Number	Description	Quantity Ordered	Quantity Rec'd	Quantity Short	Quantity Inspected	Quantity Rejected	Comment / NCR Number

Initials of Receiver QC12

Production/Admin:
 Date _____
 Received/Costing _____
 Initial _____

Location _____



Dart Aerospace Ltd.
1270 Aberdeen Street
Hawkesbury, ON K6A 1K7
Tel: 613 632 9577
Fax: 613 632 1053

PURCHASE ORDER

Purchase Order ID **PO32240**

Purchase Order Date 5/3/2016

PO Print Date 5/3/2016

Page Number 2 of 2

Order From :

VC-AD001

AIR DYNAMICS
19420B CLARK GRAHAM AVENUE
BAIE D'URFE, QUEBEC H9X 3R8

Ship To : DART AEROSPACE LTD

1270 ABERDEEN
HAWKESBURY, ON K6A 1K7
CANADA

Contact Name

Vendor Phone 514-457-4287

Ship To Contact

Ship To Phone

Ship Via: Purolator ground collect

Ship Acct:

Buyer

Customer **POID**

Customer Tax #

Terms

Currency

FOB

Chantal Lavoie

10127-2607

Net 30

CAD

EXW - (Ex Works)

PO Total:

\$2,130.00

PO Instructions: Purolator Acc#7684382

Note: Terms & Condition of Purchasing(Suppliers) and Procurement Quality Clauses are an integral part of our AS9100 requirements. To learn in detail, please visit www.dartaerospace.com for further explanation.

Change Nbr: 1

Change Date: 5/3/2016

8. Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state : Liquid.
Flash point : Closed cup: 7.22°C (45°F)
Material supports combustion. : Yes.
Color : Clear.
Odor : Not available.
pH : Not available.
Boiling/condensation point : 96.67 to 316.11°C (206 to 601°F)
Melting/freezing point : Not available.
Specific gravity : 0.84
Density (lbs / gal) : 7.01
Vapor pressure : Not available.
Vapor density : Not available.
Evaporation rate : Not available.
VOC : 804 g/l
Solubility : Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/water : Not available.

10. Stability and reactivity

Stability : Stable under recommended storage and handling conditions (see Section 7).
Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Materials to avoid : Reactive or incompatible with the following materials: acids, oxidizing materials, strong alkalis
Hazardous decomposition products : Formaldehyde.
Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
propan-1-ol	LD50 Oral	Rat	1870 mg/kg	-
	LD50 Dermal	Rabbit	4.049 g/kg	-
	LC50 Inhalation Vapor	Rat	>9800 mg/m3	4 hours
toluene	LD50 Oral	Rat	636 mg/kg	-
	LD50 Dermal	Rabbit	8.39 g/kg	-
	LC50 Inhalation	Rat	49 g/m3	4 hours
	LD50 Oral	Rat	2413 mg/kg	-
N-(3-(trimethoxysilyl)propyl) ethylenediamine	LD50 Oral	Rat	1200 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rabbit	1.28 g/kg	-



Air Dynamics **BON DE LIVRAISON**

19420B Clark Graham Avenue
Baie D'Urfé, Québec H9X 3R8

Tel.: (514) 457-4287
Fax: (514) 457-4143

PACKING SLIP 733384

CUSTOMER NO. 700

Facture à:
Invoice to:

DART AEROSPACE LTD
1270 ABERDEEN STREET
HAWKESBURY ON K6A 1K7

ACCTS PAY/ DALE BATES

Expédié à:
Ship to:

SAME

Date 06/02/16	Expédié par/Ship via: PUROLATOR COLLECT	F.A.B./F.O.B.	Conditions/Terms
------------------	--	---------------	------------------

No. de commande Purchase order no. PO32240	Date de commande Order date 05/04/16	Vendeur(se)/Salesperson BRENDA SHEA	Notre No. de commande/Our order number
--	--	--	--

Qté req/ Qty req	Expédié Shipped	En souffe/ B.O.	No. d'article Item Number	Description	Prix unitaire Unit price	Prix rapporté Extended price
2	✓	2	CA8213/F37038	ORDERED BY CHANTAL LAVOIE - SHIP VIA PUROLATOR ACCT# 7684382		
4	✓	4	BATCH	TOPCOAT - BLACK #37038 (GL KIT) MIL-PRF-85285 TY.1 (C/WCA8200B)		
4	✓	4	515X349	BATCH #		
4	✓	4	BATCH	PRIMER - GREEN (GL.KIT) SPECS: DMS2144/BMS10-79 TY.3 (C/W 910x533)		
				BATCH #B:31589 KIT LOT# 887813 EXP. MARCH 2017		
				515X349 BASE- 1 GALLON LOT# 774688		
				910X533 ACTIVATOR- 1 GALLON LOT #205765		
				CERTIFICATION/ TEST REPORTS / MSDS INCLUDED		


JE CERTIFIE PAR LES PRESENTES QUE LES PIECES D'AERONEFS
DECRIRES DANS LE PRESENT CERTIFICAT ONT ETE OBTENUES D'UNE
SOURCE D'APPROVISIONNEMENT CONFORME AUX CONDITIONS
AUXQUELLES LE CERTIFICAT D'AUTORISATION DE DISTRIBUTION
NO. 12-89 DU MINISTRE DES TRANSPORTS A ETE ATTRIBUE.

DATE

2 Juin 2016

SIGNE

Brenda Shea



I hereby certify that the aircraft parts, appliances and/or
materials described hereon were acquired from a source of
supply that is consistent with the conditions under which
the Department of Transport distributor approval
No. 12-89 has been granted.

Date:

June 2, 2016 Brenda Shea
Inspector's Signature

Material Safety Data Sheet



Date of issue 29 May 2016

Version 11.05

1. Product and company identification

Product name : 515X349 BASE COMPONENT
Code : 515X349 BASE COMPONENT
Manufacturer / Supplier : PPG Aerospace PRC-DeSoto
12780 San Fernando Road
Sylmar, CA 91342
Phone: 818 362 6711
Emergency telephone number : (412) 434-4515 (U.S.)
(514) 645-1320 (Canada)
01-800-00-21-400 (Mexico)

2. Hazards identification

Emergency overview : WARNING!
FLAMMABLE LIQUID AND VAPOR. HARMFUL IF ABSORBED THROUGH SKIN. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC RESPIRATORY AND SKIN REACTION. MAY BE HARMFUL IF INHALED OR SWALLOWED. SANDING AND GRINDING DUSTS MAY BE HARMFUL IF INHALED. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER.
Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Keep away from heat. Do not smoke. Do not breathe vapor or mist. Do not swallow. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Potential acute health effects

Inhalation : May be harmful if inhaled. Irritating to respiratory system. Can irritate eyes, nose, mouth and throat. May cause sensitization by inhalation. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion : May be harmful if swallowed.
Skin : Toxic in contact with skin. Severely irritating to the skin. May cause an allergic skin reaction.
Eyes : Severely irritating to eyes. Risk of serious damage to eyes.

Over-exposure signs/symptoms

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. NTP, IARC, and OSHA have classified chromium (+6) compounds as carcinogenic. OSHA considers all Cr+6 compounds as potential occupational carcinogens capable of causing lung cancer above the recommended exposure limits.

Medical conditions aggravated by over-exposure : Pre-existing respiratory and skin disorders and disorders involving any other target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

2. Hazards identification

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS).

See toxicological information (Section 11)

3. Composition/information on ingredients

Name	CAS number	% (w/w)
crystalline silica, respirable powder (<10 microns)	14808-60-7	10 - 30
n-butyl acetate	123-86-4	10 - 30
butanone	78-93-3	10 - 30
strontium chromate	7789-06-2	7 - 13
cyclohexanone	108-94-1	5 - 10
butan-1-ol	71-36-3	1 - 5
barium chromate	10294-40-3	0.1 - 1
carbon black, respirable powder	1333-86-4	0.1 - 1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5. Fire-fighting measures

Flammability of the product : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Extinguishing media

Suitable	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Not suitable	: Do not use water jet.
Special exposure hazards	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides

5 . Fire-fighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Use spark-proof tools and explosion-proof equipment. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not breathe vapor or mist. Ingestion of product or cured coating may be harmful. Do not swallow. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Vapors are heavier than air and may spread along floors. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Do not store above the following temperature: 120°F / 49°C.

8. Exposure controls/personal protection

Name	Result	ACGIH	Ontario	Mexico	PPG
crystalline silica, respirable powder (<10 microns)	TWA	0.025 mg/m ³ R	0.1 mg/m ³ R	0.1 mg/m ³ R	Not established
n-butyl acetate	TWA STEL	150 ppm 200 ppm	150 ppm 200 ppm	150 ppm 200 ppm	Not established Not established
butanone	TWA STEL	200 ppm 300 ppm	200 ppm 300 ppm	200 ppm 300 ppm	Not established Not established
strontium chromate	TWA STEL	0.0005 mg/m ³ (measured as Cr) Not established	0.0005 mg/m ³ (as Cr) Not established	Not established Not established	0.005 mg/m ³ Not established
cyclohexanone	TWA STEL	20 ppm S 50 ppm S	20 ppm S 50 ppm S	50 ppm S 100 ppm S	Not established Not established
butan-1-ol	TWA STEL	20 ppm Not established	20 ppm Not established	Not established 50 ppm S C	Not established Not established
barium chromate	TWA STEL	0.01 mg/m ³ (measured as Cr) Not established	0.01 mg/m ³ (as Cr) Not established	Not established Not established	0.005 mg/m ³ Not established
carbon black, respirable powder	TWA STEL	3 mg/m ³ Not established	3 mg/m ³ Not established	3.5 mg/m ³ 7 mg/m ³	Not established Not established

Key to abbreviations

A = Acceptable Maximum Peak
 ACGIH = American Conference of Governmental Industrial Hygienists.
 C = Ceiling Limit
 F = Fume
 IPEL = Internal Permissible Exposure Limit
 R = Respirable
 S = Potential skin absorption

SR = Respiratory sensitization
 SS = Skin sensitization
 STEL = Short term Exposure limit values
 TD = Total dust
 TLV = Threshold Limit Value
 TWA = Time Weighted Average

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Engineering measures : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

8 . Exposure controls/personal protection

Eyes	: Chemical splash goggles.
Hands	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: nitrile, neoprene
Respiratory	: By spraying: air-fed respirator. By other operations than spraying, in well ventilated areas, air-fed respirators could be replaced by a combination charcoal filter and particulate filter mask. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Skin	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 . Physical and chemical properties

Physical state	: Liquid.
Flash point	: Closed cup: -0.56°C (31°F)
Material supports combustion.	: Yes.
Color	: Green.
Odor	: Not available.
pH	: Not available.
Boiling/condensation point	: >37.78°C (>100°F)
Melting/freezing point	: Not available.
Specific gravity	: 1.3
Density (lbs / gal)	: 10.85
Vapor pressure	: Not available.
Vapor density	: Not available.
Evaporation rate	: Not available.
VOC	: 514 g/l
Solubility	: Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/water	: Not available.

10 . Stability and reactivity

- Stability** : Stable under recommended storage and handling conditions (see Section 7).
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Materials to avoid** : Reactive or incompatible with the following materials: acids, oxidizing materials, strong alkalis
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.

11 . Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LD50 Oral	Rat	10.768 g/kg	-
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LC50 Inhalation	Rat	>21.1 mg/l	4 hours
butanone	LD50 Oral	Rat	2737 mg/kg	-
	LD50 Dermal	Rabbit	6480 mg/kg	-
	LC50 Inhalation	Rat	11243 ppm	4 hours
Vapor	LD50 Oral	Rat	3118 mg/kg	-
	LD50 Oral	Rat	1.54 g/kg	-
	LD50 Dermal	Rabbit	0.948 g/kg	-
strontium chromate	LC50 Inhalation	Rat	8000 ppm	4 hours
	LD50 Oral	Rat	0.79 g/kg	-
	LD50 Dermal	Rabbit	3400 mg/kg	-
cyclohexanone	LC50 Inhalation	Rat	8000 ppm	4 hours
	Vapor			
	LD50 Oral	Rat	>15400 mg/kg	-
butan-1-ol	LD50 Dermal	Rabbit	>3 g/kg	-
	LD50 Dermal	Rabbit		
carbon black, respirable powder	LD50 Oral	Rat		
	LD50 Dermal	Rabbit		

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Defatting irritant

: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Target organs

: Contains material which causes damage to the following organs: blood, liver, spleen, brain, bone marrow.
Contains material which may cause damage to the following organs: kidneys, lungs, peripheral nervous system, upper respiratory tract, skin, bones, central nervous system (CNS), ears, eye, lens or cornea.

Carcinogenicity

Carcinogenicity : Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.

Classification

11 . Toxicological information

Product/ingredient name	ACGIH	IARC	NTP
crystalline silica, respirable powder (<10 microns)	A2	1	Known to be a human carcinogen.
strontium chromate	A2	1	Known to be a human carcinogen.
cyclohexanone	A3	3	-
barium chromate	A1	1	Known to be a human carcinogen.
carbon black, respirable powder	A3	2B	-

Carcinogen Classification code:

ACGIH: A1, A2, A3, A4, A5

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

Not listed or regulated as a carcinogen: -

12 . Ecological information

Environmental effects : No known significant effects or critical hazards.

13 . Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	TDG	Mexico	IMDG
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	3	3	3
Packing group	II	II	II
Environmental hazards	Yes.	No.	Yes.
Marine pollutant substances	(strontium chromate)	Not applicable.	(strontium chromate)

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Use spark-proof tools and explosion-proof equipment. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not breathe vapor or mist. Do not swallow. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Vapors are heavier than air and may spread along floors. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Do not store above the following temperature: 120°F / 49°C.

STRAIGHT BILL OF LADING CONNAISSEMENT

ORIGINAL

NOT NEGOTIABLE / NON NÉGOCIABLE

ClearLanguage
LangageClair

Shipper Reference No./
No de référence de l'expéditeur

119311

Carrier Reference No./
No de référence du transporteur

June 2, 2016

PUROLATOR

Date

(Name of Carrier / Nom du transporteur)

TO/À: DART AEROSPACE LTD.

Consignee / Consignataire

On Collect on Delivery shipments, the letters "COD" must appear before consignee's name
Si les marchandises sont payables à la livraison, inscrire les lettres "COD" avant le nom du consignataire

FROM/DE:

Shipper / Expéditeur AIR DYNAMICS CO. LTD.

Street / Rue 1270 ABERDEEN STREET

Street / Rue 19420B CLARK GRAHAM AVE.

Destination HAWKESBURY, ON Postal Code / Code postal K6A 1K7

Origin / Origine BAIE D'URFE, QC H9X 3R8

Route

Vehicle No
N° du véhicule

No. of Units & Container Type Nbre d'unités & type de contenant	DG MD	DESCRIPTION Proper Shipping Name/Hazard Class/Identification Number/Packing Group Appellation réglementaire/Classe/Numéro d'identification/Groupe d'emballage	TOTAL QUANTITY (Weight, Volume, kg, Litre, etc.) QUANTITÉ TOTALE (Poids, volume, kg, Litre, etc.)	WEIGHT (Subject to Correction) POIDS (Sujet à corrections)	RATE TAUX	CHARGES (For Carrier Use Only) FRAIS (Pour transporteur seulement)
2 boxes	X	UN1263, PAINT, Class 3, PG II		37 kgs		
		Shipper's Ref: PO#PO32240,				
		Inv# 142185				
2 boxes				37 kgs		

Type and number of placards/
Type et nombre de plaques

Emergency Response Assistance Plan number (ERAP)/
Numéro du Plan d'intervention d'urgence (PIU)

EMERGENCY TELEPHONE NUMBER/24-HOUR NUMBER/ CHEMTREC; 800-424-9300
NUMÉRO DE TÉLÉPHONE D'URGENCE/NUMÉRO 24-HEURES

REMIT C.O.D. TO: / VERSEMENT DES SOMMES PAYÉES À LA LIVRAISON:

ADDRESS / ADRESSE:

NOTE: Where the rate is dependent on value, shippers are required to state specifically in writing the agreed or declared value of the property.
The agreed or declared value of the property is hereby specifically stated by the shipper to be not exceeding

NOTE: Lorsque le taux est relatif à la valeur, les expéditeurs sont obligés de mentionner spécifiquement par écrit, la valeur déclarée convenue de la propriété.
La valeur déclarée ou convenue de la propriété est, par les présentes, spécifiquement déclarée par l'expéditeur comme étant égale ou inférieure à

\$ par

\$ par

PAYABLE À LA LIVRAISON

COD

Amt. / Montant: \$

The carrier shall not make delivery of this shipment without payment of freight and all other lawful charges.
Le transporteur ne livrera la marchandise que si les frais de transport et tous les autres frais légitimement encourus sont payés.

(Signature of Consignor / Signature du l'expéditeur)

C.O.D. FEE

FRAIS D'ENVOI CONTRE REMBOURSEMENT
PREPAID PAYÉ D'AVANCE ☐ COLLECT À PERCEVOIR ☐

TOTAL CHARGES:
TOTAL DES FRAIS: \$

FREIGHT CHARGES / FRAIS DE TRANSPORT
FREIGHT PREPAID except when box at right is checked
FRAIS PAYÉS D'AVANCE sauf si la case de droite est cochée
(Check box if charges are to be collect)
Cocher la case si les frais sont à percevoir

RECEIVED, subject to the classifications and tariffs in effect on the date of the issue of this Bill of Lading, the property described above in apparent good order, except as noted (contents and condition of contents of packages unknown), marked, consigned, and destined as indicated above which said carrier (the word carrier being understood throughout this contract as meaning any person or corporation in possession of the property under the contract) agrees to carry to its usual place of delivery at said destination, if on its route, otherwise to deliver to another carrier on the route to said destination. It is mutually agreed as to each carrier of all or any of, said property over all or any portion of said route to destination and as to each party at any time interested in all or any said property, that every service to be performed hereunder shall be subject to all the bill of lading terms and conditions in the governing classification on the date of shipment.

Shipper hereby certifies that he is familiar with all the bill of lading terms and conditions in the governing classification and the said terms and conditions are hereby agreed to by the shipper and accepted for himself and his assigns.

REÇU, sous réserve des taux et des classifications en vigueur à la date d'émission de ce connaissement, les marchandises ci-dessus décrites en bon état apparent (le contenu des colis et sa condition étant inconnus) marquées, contresignées et destinées tel que ci-dessus mentionné, que le dit transporteur (dans le présent contrat, on entend par "transporteur" toute personne ou corporation en possession de la propriété sous contrat) consent à transporter et à délivrer à leur consignataire au point de destination si ce point se trouve sur la route qu'il est autorisé à desservir, sinon à faire transporter ou délivrer par un autre transporteur autorisé à ce faire. Il est mutuellement convenu que chaque transporteur transportant les dites marchandises en vue ou en vertu sur le parcours entier ou une portion quelconque de celui-ci jusqu'à destination et que tout intéressé à la dite ou toute autre expédition pour tout service à effectuer en vertu des présentes est sujet à toutes les conditions du connaissement suivant la classification en vigueur à la date de l'expédition.

Par les présentes, l'expéditeur certifie qu'il a pris connaissance de toutes les conditions du connaissement suivant la classification en vigueur et, que ces dites conditions sont par les présentes acceptées par l'expéditeur pour lui-même et ses ayants-droits.

SHIPPER M. Truesdale
EXPÉDITEUR

CARRIER
TRANSPORTEUR

CONSIGNEE
CONSIGNATAIRE

PER
PAR

PER
PAR

PER
PAR

DATE June 2, 2016

DATE

DATE

ORIGINAL - NOT NEGOTIABLE / NON NÉGOCIABLE

(THIS DOCUMENT WHEN ISSUED AS A RAIL BILL OF LADING IS TO BE SIGNED BY THE SHIPPER AND AGENT OF THE CARRIER ISSUING SAME)

(UN TEL DOCUMENT ÉMIS COMME CONNAISSEMENT LORS DU TRANSPORT DE MARCHANDISES PAR RAIL DOIT ÊTRE SIGNÉ PAR L'EXPÉDITEUR ET L'AGENT DU CAMIONNEUR)

Printed in Canada
Imprimé au Canada

03/06



Dart Aerospace Ltd.
1270 Aberdeen Street
Hawkesbury, ON K6A 1K7
Tel: 613 632 9577
Fax: 613 632 1053

PURCHASE ORDER

Purchase Order ID PO32240

Purchase Order Date 5/3/2016

PO Print Date 5/3/2016

Page Number 1 of 2

Order From :

VC-AD001

AIR DYNAMICS
19420B CLARK GRAHAM AVENUE
BAIE D'URFE, QUEBEC H9X 3R8

Ship To : DART AEROSPACE LTD

1270 ABERDEEN
HAWKESBURY, ON K6A 1K7
CANADA

E-MAILED

MAY 04 2016

Contact Name

Vendor Phone 514-457-4287

Ship To Contact

Ship To Phone

Ship Via:

Purolator ground collect

Ship Acct:

Buyer

Chantal Lavoie

Customer POID

Customer Tax #

10127-2607

Terms

Net 30

Currency

CAD

FOB

EXW - (Ex Works)

Line Nbr	Reference Vendor Part Number Line Comments Delivery Comments	Description/ Mfg ID	Req Date/ Taxable Promise Date	CD	Req Qty/ Unit of Measure	PO Unit Price	Extended Price
1	71400-11	CA8213/F37038 TOPCOAT COLOR BLACK CAMOUFLAGE	6/2/2016		2.00 Each	\$265.00	\$530.00
Procurement Quality Clauses			Yes				
A005 RIGHT OF ENTRY			6/2/2016				
A014 SHELF LIFE CONTROLLED MATERIAL; 70% SHELF							
LIFE REQUIRED AT RECEIPT							
A026 CERTIFICATION OF MATERIAL CONFORMANCE							
A040 NOTIFICATION OF QUALITY ESCAPE							
A042 DART NOTIFICATION BY SUPPLIER							
A043 RETENTION OF QUALITY DOCUMENTS							

Line Total: \$530.00

Deliver To: ANDY

2	71400-11	515X349 PRIMER GREEN	6/2/2016		4.00 Each	\$400.00	\$1,600.00
			Yes				
			6/2/2016				

Line Total: \$1,600.00

Deliver To: ANDY

PO Instructions: Purolator Acc#7684382

Note:

5/3/2016

**RELEASE
CERTIFICATE**


AIR DYNAMICS

19420B Clark Graham Avenue
Baie d'Urfé, Québec, H9X 3R8

514-457-4287

AD-1(A)

QTY. 4



NOMENCLATURE

PRIMER - GREEN (GL KIT)

PART NUMBER

515X349

MODEL or TYPE

(2 Specs - DM52144
+ BM510-79)

MAKE

PRC - PPG

SERIAL NUMBER

164(515X349) LOT# 774688 (EXP. March 2017)
164910 X 533 LOT# 205765

NEW

REPAIRED

INSPECTED

OVERHAULED

MODIFIED

PREVIOUS CERTIFICATION

B# 31589 KIT LOT# 887813

I HEREBY CERTIFY THAT THE AIRCRAFT PARTS, APPLIANCES AND/OR MATERIALS DESCRIBED HEREON
WERE ACQUIRED FROM A SOURCE OF SUPPLY THAT IS CONSISTANT WITH THE CONDITIONS UNDER
WHICH THE DEPARTMENT OF TRANSPORT DISTRIBUTOR APPROVAL NO. 12-89 HAS BEEN GRANTED.

DATE

June 2, 2016

Brenda Sheen

INSPECTOR'S SIGNATURE

SECURITES DANS LE PRESENT CERTIFICAT ONT ETE OBTENUES D'UNE
SOURCE D'APPROVISIONNEMENT CONFORME AUX CONDITIONS
AUXQUELLES LE CERTIFICAT D'AUTORISATION DE DISTRIBUTION
NO. 12-89 DU MINISTERE DES TRANSPORTS A ETE ATTRIBUE.

DATE

SIGNE

2 juin 2016
R. Bouda
proa

